# 465N-5606-0041 FLASH PATTERN

**LIGHTBAR LAMP CONFIGURATION**

DF3 DF2 DF1 PF1 PF2 PF3
DC PC

| MODE | CONTROL WIRES ACTIVATED | LAMP OPERATION |
|---|---|---|
| | | FRONT / CORNER STROBES |
| 0 | NONE | NONE |
| 1 | ORG (ALL STROBES) | DF3 & PF3 SIMULTANEOUS AND ALTERNATE WITH DF2 & PF2 SIMULTANEOUS (6 PULSES PER BURST) DF1 ALTERNATES WITH PF1 DC ALTERNATES WITH PC (3 PULSES PER BURST) |
| 2 | ORG & BLU | SAME AS MODE 1 |
| 3 | ORG & WHT/BLK | SAME AS MODE 1 |
| 4 | ORG & BLU & | SAME AS MODE 1 |
| 5 | BLU | NONE |

## CONTROL WIRES FOR OPTIONAL HALOGENS

| CONTROL WIRE ACTIVATED | HALOGEN LAMP |
|---|---|
| BRN | DF1 & PF1 (SPLIT TAKEDOWN) OR DF2 & PF2 (SPLIT TAKEDOWN) |

## CONTROL WIRES FOR OPTIONAL PREEMPTION

| CONTROL WIRE ACTIVATED | FUNCTION |
|---|---|
| BROWN/WHITE | PARKING BRAKE OVERRIDE |

**NOTES:**

1. **GREEN control wire activates high intensity to strobes.**
2. **Apply +12vdc to appropriate control wire to activate desired function.**